





В Performance standard correction as per SAE J1349; 60° F / 15.5° C; Baro 29.92 in. / 101.3 mB Е Α 400 924 27.6 350 808 246 24.1 300 693 211 20.7 250 577 176 17.2 13.8 200 462 141 150 346 106 10.3 100 231 70 50 115 35 3.4 С 10 20 30 50 70 100 D 38 76 114 151 189 227 265 303 341 379 B Pressure in PSI C Flow U.S. GPM D Flow litters / Min. E Head Press. Feet F Head Press. Meter

PORTABLE FOUR STAGE HIGH PRESSURE FIRE PUMP

- For Emergency Rescue Equipment used by forestry and other emergency services
- The WICK® 375 is a world leader in portable high pressure fire pumps capable of moving water over long distances
- Powered by a 10 HP, 210 cc modern 2-stroke, air cooled Solo engine
- Electronic over-speed protection cut-out switch (patented)
- Detachable 4-stage foam-compatible pump using a one piece stainless steel clamp
- Nikasil cylinder wall for extended wear and low maintenance
- User friendly and easy pull starting
- Detachable rewind starter for emergency rope start
- See chart for available fuel connection models
- U.S.D.A. qualified to meet Specification 5100-274C
- Available with transportable back pack

WEIGHT & DIMENSIONS

Length	22.75"	57.8 cm
Width	14.25"	36.2 cm
Height	14.25"	36.2 cm
Weight	56.0 lbs	25.4 kg
Suction	2.0" NPSH	50 mm
Discharge	1.5" NPSH	38 mm

ENGINE

Solo	2 stroke; 210 cc; 10.0 Hp / 7.5 kw
Ignition	Flywheel magneto; solid state; breaker less
Cylinder	Nikasil cylinder wall

Cylinder

Lighting coil 20 Watts

Specifications subject to change without notice



WICK'375

BID SPECIFICATION

- The portable fire pump must have a 10 HP, 210cc 2-stroke Solo engine
- The pump must be equipped with an electronic over-speed protection cut-out switch
- The pump must be equipped with an electronic ignition
- The pump must not weigh more than 56 lbs / 25 Kg
- The engine cylinder walls must be Nikasil treated
- The pump must be equipped with a detachable 4 stage foam compatible pump end that is attached to the engine using a one piece stainless steel clamp
- The pump must have a detachable rewind starter for emergency rope start.
- The pump must be available with Chrysler, Mercury, SAE, Yamaha or USDA style fuel quick-connect
- The pump must be U.S.D.A. qualified to meet Specification 5100-274C. This primary coding must be at least C-60-200/40 and secondary coding must be at least C-60-175/50 and C-60-150/60
- The pump must be available with a transportable back pack.
- The pump must have minimum flow and pressures as shown in the performance chart on the opposite page
- The four stage pump must be painted RED



Part#	Description
71WICK375-A	WICK® 375 Fire Pump - Mercury fuel connection
71WICK375-C	WICK® 375 Fire Pump - Chrysler fuel connection
71WICK375-SAE	WICK® 375 Fire Pump - SEA fuel connection
71WICK375-Y	WICK® 375 Fire Pump - Yamaha fuel connection
71WICK375-YNZ	WICK® 375 Fire Pump - Yamaha fuel connection (New Zealand) ind Heat Shield & Spark arrestor
71WICK375-USDA	WICK® 375 Fire Pump - USDA
71WICK375-ASWD	WICK® 375 Fire Pump - Mercury fuel connection ∕ Special Sweden



OPTIONAL

	Part#	Description	
A	71W37-HPACK	Back board for carrying	
В	70FLPFT5	Fuel Tank 6.6 US Gal. / 25 Liters *	
C 1	70FLPFL-M	Fuel Line Complete (Mercury)	
C2	70FLPFL	Fuel Line Complete (Chrysler)	
C3	70FLPFL-Y	Fuel Line Complete (Yamaha)	
C4	70FLPFL-MAN	Fuel Line Complete Mercury Female (Manitoba)	
C5	70FLPFL-GSA	Fuel Line Complete with SAE swivel Female at both ends	
C5	70FLPFL-NB	Fuel Line Complete with SAE swivel Female at both ends extended length	
C6	70FLPFL-USDA	Fuel Line Complete (USDA)	
D1	70FLHPPQC	Hand Primer QC	
D2	70FLHPPPS	Hand Primer NPSH	
D2	70FLHPPNH	Hand Primer NH	
E	70FL15TPPS	Thread protector 1 ½" / 38mm	
E	70FL20TPPS	Thread protector 2" / 51mm	
E	6124NM24PF	Adaptor 1 ½" / 38mm NH Male x 1 ½" / 38mm NPSH Female	
F	71W37-SPKARR	Spark Arrestor	
G	70FL20DLPS10	Draftlite HP suction hose $2''/51$ mm x $10'/3$ M c/w NPSH *	
Н	70FLFV2PF	Foot Valve / Strainer 2"/51mm NPSH Female *	
* See	* See website for complete listing of accessory and related products		

"See website for complete listing of accessory and related product

© 2023 Mercedes Textiles Limited LO2G /JH ® Represents registered trademarks of Mercedes Textiles Limited, unless otherwise noted ™ Represents trademarks of Mercedes Textiles Limited, unless otherwise noted